


# COBRA 65 DRI



**PATENTED DUAL MIXED ROTOR™**  
equipped with 20 hammers, with inserts, and 4 blades.



**COMPLETE DRI SOUND-PROOF COWLING**  
Allows complete access to all of the machine's part



**HOPPER**  
Transparent safety screen. Safe and easy-to-use electric controls. Standard air inlet under metallic feed belt improves ventilation by 25% - standard width 40 cm.



**PERKINS ENGINE**  
PERKINS 4-cylinder 65 hp engine equipped with Silent blocs.



**CLUTCH**  
Hydraulic safety clutch.  
180° thermal safety.  
145° thermal safety.

**OPTIONAL CO2 REDUCTION**



**NEW VARIOSTRESS UNIT WITH REAR-LIT SCREEN**  
Pre-set No Stress program adjustable for the type of material to be processed.

## TECHNICAL CHARACTERISTICS

Art number	1425505
Engine	PERKINS 65 hp / 47,81 kw
Engine swept / volume cm <sup>3</sup>	3300 / 4-cyl.
Fuel	Diesel
Cowling	DRI soundproofing
Admissible diameter	20 cm
Output	40 m <sup>3</sup> /h
Rotor diameter	560 mm
Rotor weight	200 kg
Hammers	20
Knives	4
Feeder	1
Feed roll width	500 mm
Feed roll diameter	395 mm
Allowable road weight axles	2 500 kg
No. of axles	1
Tyre dimensions	215 x 14
Tank capacity	50 L
Consumption	6 L/h
Multidirectional chimney	180 °
Chimney outlet height	2 250 mm

Machine directive : 2006/42/CE.

Machine weight	2 050 kg
PTAC trailer approval	2 100 kg
Hopper dimensions (L x W)	1 600 x 1 680 mm
Hopper loading height	700 mm
L x W x H	4 400 x 1 850 x 2 500
Guaranteed acoustical power level rating	125 dBA

## OPTIONS

Option CO2 Reduction	1425204
Insert ref.	RHEV/0010 (20)
Knife ref.	RHEV/0020 (4)
Spare wheel ref + spare wheel support ref.	1425920
Wheel chock ref. (2)	ECIPRE/0010
Stabilizer legs ref.	ECIMV/0325

Harmonized standards used : EN 13525.



TS INDUSTRIE GmbH  
Weserstrasse 2 - 47506 NEUKIRCHEN-VLUYN  
DEUTSCHLAND  
Telefon +49(0)2845 9292-0  
Telefax +49(0)2845 9292-28  
kontakt@ts-industrie.eu

[www.ts-industrie.eu](http://www.ts-industrie.eu)